



## PRODUCT DATA SHEET

### EXN - Carios SAE 5W40 API SN/CF - Fully Synthetic

*Super Ultimate Protection Engine Oil Design*

#### DESCRIPTION

A blend of premium fully synthetic base oils and the latest generation based on HC-Synthesis. It perfectly protects from wear, especially under city traffic conditions. It's good wear protection and lubrication properties remain unchanged even under extreme operation. It can be used for all new and old engines using flex-fuel blended with ethanol and It is recommended for all types of modern gasoline and diesel passenger cars, SUVs, light vans and trucks.

#### FEATURES AND ADVANTAGES

- \* Meets or exceeds the latest OEM and industry approvals
- \* Reduces maintenance costs
- \* Provides superior protection against friction
- \* Prevents accumulation of sludge and corrosion
- \* Does not thicken due to formation of soot

#### PRODUCT PERFORMANCE CLAIM

STANDARDS \* API SN/SM/SL/CF, ACEA A3/B3-12, ACEA A3/B4-12

APPROVALS \* BMW Longlife - 01, MB-Approval 229.5, Porsche A40, Renault RN0700/RN0710,

#### TECHNICAL DATA PROPERTIES

PARAMETER	METHOD	Typical Result
Viscosity Grade	SAE J300	5W40
Colour	ASTM D1500	3
Density @ 15oC	ASTM D4052	0.86
Kinematic Viscosity @ 40°C	ASTM D7042	76
Kinematic Viscosity @ 100°C	ASTM D7042	13.55
Viscosity Index	ASTM D2270	178
Flash Point, °C	IP 523	230
Total Base Number	ASTM D2896	7.9
Pour Point, °C	ASTM D97	-40
Cold Crank Visc @ -30°C	ASTM D5293	6140



**Product Number : E-GE-5W40-FS**

**Available Pack : 1L & 4L**

**VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

#### HEALTHY AND SAFETY

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

