

PRODUCT DATA SHEET

EXN - Motios 4T - SAE 10W40 API SM/JASO MA2 - SEMI SYNTHETIC HIGH PERFORMANCE MOTOR DESIGN

DESCRIPTION

EXN - Motios 4T - SAE 10W40 is a **semi synthetic** lubricant developed for the engines of four-stroke motorcycles. It can be safely used for four-stroke, high performance and air- or water-cooled motorcycles. It is suitable for motorcycles built in Europe and in Japan with JASO MA2 specifications are recommended. The oil is a blend of synthetic/hydrocracked premium base oils and special additives which protects against high temperature oxidation, wear, and viscosity breakdown.

FEATURES AND ADVANTAGES

- * JASO MA2 approved to warranty a perfect lock up of wet clutch
- * Reduces maintenance costs and easy gear shifting
- * Protects from wear, corrosion and foaming
- * High viscosity index ensure high stability in heavy duty conditions
- * Reduces sedimentation on the pistons
- * Recommended for all types of motorcycles



PRODUCT PERFORMANCE CLAIM

STANDARDS * API SM, JASO MA2

TECHNICAL DATA PROPERTIES

Viscosity grade	SAE J 300	10W-40 - Semi
Colour	ASTM D1500	2.5
Density @ 15°C	ASTM D4052	0.860
Kinematic Viscosity @ 40°C	ASTM D7042	95.5
Kinematic Viscosity @ 100°C	ASTM D7042	14.2
Viscosity Index	ASTM D2270	145
Flash Point, °C	IP 523	220
Total Base Number	ASTM D2896	6.00
Pour Point, °C	ASTM D97	-30
Cold Crank Visc @ -25°C	ASTM D5293	6450

Product Number : E-MC-4T-10W40SM-SS

Available Pack : 1L, 4L, 18L & 200L

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

